

Sapphire Water Chiller

Undersink

140 W, chill capacity 14 L/H



Usage


Undersink water chiller to be used with a counter mounted tap and filter to provide instant, high quality chilled drinking water.

p.26

Features and Benefits

- Add to your Zen Spa to provide boiling and chilled water through your 2 in 1 Zen Spa tap
- Team with one of our Zen Ice or Crystal Pure drinking water taps for chilled drinking water solutions
- Designed to fit in a standard kitchen undersink cupboard
- In office environments avoids the need for space to be taken up by a floor standing chiller unit
- Simple to use
- Ideal for light commercial and domestic applications
- Chill capacity 14 litres or 80 glasses per hour (glass 167 ml)
- 2 litres immediate draw off
- Flow rate 2 l/pm when chiller used with Zen tap and connected to F1T filter.
- Plumbed in system gives reduced costs over bottle fed coolers - connects directly to the mains water supply
- Chilled water temperature adjustable from 8°C to 12°C
- All our taps for use with the Sapphire chiller are suitable for filling sports bottles and carafes
- Helps reduce single use plastic
- Consider the Zen Font with Drain (page 18) for a stylish sleek solution when mounting the tap over a sink is not possible or desired.

Product Code	Chill Capacity (litres/ hour)	Glasses per hour (167ml glass)	Power (kW)
SAPUC2	14	80	0.14

**Outer Casing**

White powder coated steel

Capacity

80 glasses per hour
(based on 167 ml glass)

Maintenance

Sanitise every 3 - 6 months.

Change filter approximately every 6 months.

See product instructions for full maintenance requirements.

Refrigerant Type

R290/ 25g

IP Rating

IP20

Power (kW)

0.14

Current (amps)

0.6

Installation

Chilling requires the ambient installation environment temperature to be between 10°C and 38°C.

Plumbing

Must be installed by a suitably qualified person.

Minimum water pressure 1 bar.

Maximum water pressure 3 bar.
If higher than this a pressure reducing valve is required.

Electrical Connection

Supplied with a pre-wired (1.85m) black kettle lead cable BS plug.

Class I

Approvals

CE, UKCA, WRAS

Standard Warranty

2 years parts or replacement warranty.

Product Code	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)
SAPUC2	360	180	380	11.1